Product Catalogue Cooking and Counters 2022



making food irresistible

MARB

THE KITCHEN

BREW

..... BAIRY & IUICE

OD TO GO

Fri-Jado: making food irresistible.

Pleasing the five senses: that's what it's all about when customers enter your store. Your deli or food-to-go department should therefore be a clear showpiece that provides a true food experience.

At Fri-Jado, we believe that an innovative and appetizing food experience can truly enrich any food retail environment. We provide food retailers around the world with the latest technology that makes their food products stand out. We engage their customers in the food preparation process with eye-catching front-cooking solutions. When it comes to fresh food presentation, our heated and refrigerated counters provide a crystal clear product view combined with perfect holding conditions.

Everything we do is about creating the best stage for our customers' products. We are convinced that creating maximum attraction through superior preparation and irresistible presentation is the most effective way to boost fresh food sales. Equally important, food retail equipment should have the lowest total cost of ownership. Hence, it is our passion to continuously improve the food retail experience with the latest high-quality technological innovations. At the same time, we realize that technology is just a tool. Putting our customers' products on stage is what we really do.



Why Fri-Jado?

Technology as enabler

Everything we do revolves around putting our customers' products on stage. We believe that creating maximum attraction towards food retail customers through superior quality and irresistible presentation is the most effective way to boost fresh food sales. Our technology is 'just' a tool that we developed around this philosophy.

Innovation

We are on top of new trends in technology, design and ergonomics with the aim of continuously improving the food retail experience. We regularly discuss the latest market trends and opportunities with our partners and international food retail customers. This is how we translate innovation into customer value in our products.

Highest quality

Providing value means providing technology that works, each and every time. All our equipment is developed and produced according to the highest standards. The result: first-class equipment with the lowest total cost of ownership in the industry.

Hot meets cold

The ultimate food experience combines both hot and cold products that are fresh, ready-to-heat or ready-toeat. Our collection features products for hot and cold food preparation and presentation, which is unique in the industry.

Global network

We have been a reliable partner for food retail solutions since 1937. Our proven track record and solid international network of sales offices and local service partners provides a strong base.



| NEW: Fri-Jado GO Combi Steamer | |
|--|--|
| NEW: Multi Deck Display hot self-serve | |

Cooking

| Auto Clean Rotisseries - TDR auto-clean TDR 5 s auto-clean TDR 8 s auto-clean SmartConnect Fri-Jado Rotisserie Cleaner - for TDR auto-clean | 12 12 12 14 17 |
|---|----------------------------|
| Auto Clean Rotisseries - Multisserie | 18 |
| Multisserie with disposable waste bags | 18 |
| Multisserie with grease separator | 18 |
| Electric 5-spit Rotisseries | 20 |
| TDR 5 Programmable eco | 20 |
| TDR 5 Manual | 20 |
| Electric 8-spit Rotisseries | 22 |
| TDR 8 Programmable eco | 22 |
| TDR 8 Manual | 22 |
| Combinations Rotisserie and Multi Deck | 24 |
| Space Saver TDR 5 P with Multi Deck | 24 |
| Space Saver TDR 5 M with Multi Deck | 24 |
| Combi Steamer - GO Combi | 26 |
| GO Combi 1.06 | 26 |
| GO Combi 1.10 | 26 |
| Fri-Jado Essentials | 28 |
| Turbo Grill rotisserie - 4 spits | 28 |
| Convenience Store Displayer - 3 level | 28 |

Counters

| Grab-and-Go Heated Displays - Multi Deck Displays | 32 |
|--|---------|
| Multi Deck Display 60/90/120 - 3 level | 32 |
| Multi Deck Display 60/90/120 - 4 & 5 level | 34 |
| Accessories Multi Deck Displays | 37 |
| Grab-and-Go Heated Displays - Multi Deck Essential | 38 |
| Multi Deck 60/100/120 - 5 level square | 38 |
| Grab-and-Go Heated Displays - Multi Deck curved | 40 |
| Multi Deck 60/100/120 - 4 & 5 level curved | 40 |
| Heated Deli Counters | 42 |
| Hot Deli 3/4/5 square | 42 |
| Hot Deli 3/4/5 curved | 44 |
| Convenience Counters - Hot | 46 |
| Modular Convenience Counter - 2 level | 46 |
| Modular Convenience Counter - 2 level drop-in | 48 |
| Modular Convenience Counter - 3 & 4 level | 50 |
| Modular Convenience Counter - 3 & 4 level drop-in | 52 |
| Accessories MCC Hot self-serve | 55 |
| Convenience Counters - Cold | 56 |
| Modular Convenience Counter - 2 level | 56 |
| Modular Convenience Counter - 2 level drop-in | 58 |
| Modular Convenience Counter - 3 & 4 level | 60 |
| Modular Convenience Counter - 3 & 4 level drop-in | 62 |
| Notes | — 64 |
| Disclaimer | 66 |
| | |

Counters



Boost sales!

Changes in consumer lifestyles have contributed to the increased popularity of grab-and-go products and ready-to-eat meals.

An appetizing product presentation is the key to **stimulating impulse sales** of these hot and refrigerated products. Our heated and refrigerated merchandisers have been designed with this idea in mind. Thanks to **excellent product visibility** and **superior holding technology**, products look irresistible and stay delicious for hours.

Your advantages

- Increase impulse sales
- Food quality and food safety
- Low operating costs



Convenience Counters 2 level - Hot

Increases food-to-go sales: excellent product presentation Modular design: easy to install, adapt to any store format Space-saving: ideal for areas with limited floor space **Flexibility**: available in various widths as drop-in version or with underframe

Food safety, longer shelf life: superior holding technology

Modular Convenience Counter self serve (available from 1 May 2022)



Features

- 2 level heated open self-serve display cabinet
- Designed for packaged products
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable angle
- Patented Hot Blanket holding technology
- Energy saving hot air recirculation technology
- Total display area:
 - MCC H SS 60-2: 0,44 m²
 - MCC H SS 90-2: 0,77 m²
 - MCC H SS 120-2: 1,06 m²

Available models

- Backloading
- Solid back (control panel customer side)

Optional accessories

- Castor set
- Bumper set
- Price rail set Front door set
- Merchandising accessories (see page 55)

Modular Convenience Counter self serve humidified with doors (available from 1 May 2022)



- Features
- 2 level heated self-serve display cabinet with front doors
- Humidified to maintain the quality of unpackaged products
- Manual water fill (backloading version only) or automatic water fill
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable angle and height
- Energy saving hot air recirculation technology
- Total display area:
 - MCC H SS FD 60-2: 0,51 m²
 - MCC H SS FD 90-2: 0,81 m²
 - MCC H SS FD 120-2: 1,12 m²

Available models

- Backloading
- Solid back (control panel customer side)*
- *Can only be connected to an external water supply

Optional accessories

- Castor set
- Bumper set
- Price rail set

Modular Convenience Counter full serve humidified (available from 1 May 2022)



Features

- 2 level heated full serve display cabinet Humidified to maintain the quality of
- unpackaged products
- Manual or automatic water fill
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side
- Slim shelves with adjustable angle and height
- Energy saving hot air recirculation technology
- Total display area:
 - MCC H FS 60-2: 0,51 m²
 - MCC H FS 90-2: 0,81 m²
 - MCC H FS 120-2: 1,12 m²

Available modelsBackloading

Optional accessories

- Castor set
- Bumper set
- Price rail set

| | MCC Hot self serve | MCC Hot self serve humidified with doors | MCC Hot full serve humidified |
|---------------------------------------|--------------------|---|----------------------------------|
| | | | |
| | Number | Number | Number |
| MCC 60 | | | |
| MCC 60 2 level with stand | 9389211 | 9389237 | 9389231 |
| MCC 60 2 level with stand solid back | 9389212 | 9389238* | |
| MCC 90 | | | |
| MCC 90 2 level with stand | 9389213 | 9389239 | 9389233 |
| MCC 90 2 level with stand solid back | 9389214 | 9389240* | |
| MCC 120 | | | |
| MCC 120 2 level with stand | 9389215 | 9389241 | 9389235 |
| MCC 120 2 level with stand solid back | 9389216 | 9389242* | |
| | | * can only be connected to an external water supply | |

Dimensions MCC

| Width MCC 60 | 600 mm | 600 mm | 600 mm |
|--------------------|-----------|-----------|-----------|
| Width MCC 90 | 900 mm | 900 mm | 900 mm |
| Width MCC 120 | 1200 mm | 1200 mm | 1200 mm |
| Depth | 750 mm | 750 mm | 750 mm |
| Height on stand | 1420 mm | 1420 mm | 1420 mm |
| Technical data MCC | | | |
| Power MCC 60 | 1,36 kW | 1,72 kW | 1,72 kW |
| Power MCC 90 | 2,04 kW | 2,09 kW | 2,09 kW |
| Power MCC 120 | 2,73 kW | 2,79 kW | 2,79 kW |
| Voltage | 1N~ 230 V | 1N~ 230 V | 1N~ 230 V |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |

| Accessories* | MCC Hot self serve | MCC Hot self serve humidified with doors | MCC full serve humidified |
|---------------------------------------|--------------------|---|------------------------------|
| Description | Number | Number | Number |
| Price rail set MCC 60 - 2 level | 9389807 | 9389815 | 9389815 |
| Price rail set MCC 90 - 2 level | 9389808 | 9389816 | 9389816 |
| Price rail set MCC 120 - 2 level | 9389809 | 9389817 | 9389817 |
| Bumper MCC 60 | 9380206 | 9380206 | 9380206 |
| Bumper MCC 90 | 9380207 | 9380207 | 9380207 |
| Bumper MCC 120 | 9380205 | 9380205 | 9380205 |
| Castor Set (total height MCC + 23 mm) | 9389851 | 9389851 | 9389851 |
| Front door set MCC 60 - 2 level | 9389835 | | |
| Front door set MCC 90 - 2 level | 9389836 | | |
| Front door set MCC 120 - 2 level | 9389837 | | |

*See page 55 for Merchandising accessories Hot self serve models.

Convenience Counters 2 level - Hot drop-in

Increases food-to-go sales: excellent product presentation Modular design: easy to install, adapt to any store format Space-saving: ideal for areas with limited floor space

Flexibility: available in various widths as drop-in version or with underframe

Food safety, longer shelf life: superior holding technology

Modular Convenience Counter self serve drop-in (available from 1 May 2022)



Features

- 2 level heated open self-serve display cabinet
- Designed for packaged products
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable angle
- Patented Hot Blanket holding technology
- Energy saving hot air recirculation technology
- Total display area:
 - MCC H SS 60-2: 0,44 m²
 - MCC H SS 90-2: 0,77 m²
 - MCC H SS 120-2: 1,06 m²

Available models

- Backloading
- Solid back (control panel customer side)

Optional accessories

- Price rail set
- Front door set
- Merchandising accessories (see page 55)

Modular Convenience Counter self serve humidified with doors drop-in (available from 1 May 2022)



Features

- 2 level heated self-serve display cabinet with front doors
- Humidified to maintain the quality of unpackaged products
- Manual water fill (backloading version only) or automatic water fill
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable angle and height
- Energy saving hot air recirculation technology
- Total display area:
 - MCC H SS FD 60-2: 0,51 m²
 - MCC H SS FD 90-2: 0,81 m²
 - MCC H SS FD 120-2: 1,12 m²

Available models

- Backloading
- Solid back (control panel customer side)*
- *Can only be connected to an external water supply

Optional accessories

Price rail set

Modular Convenience Counter full serve humidified drop-in (available from 1 May 2022)



Features

- 2 level heated full serve display cabinet Humidified to maintain the quality of
- unpackaged products
- Manual or automatic water fill
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side
- Slim shelves with adjustable angle and height .
- Energy saving hot air recirculation technology .
- Total display area:
 - MCC H FS 60-2: 0,51 m²
 - MCC H FS 90-2: 0,81 m²
 - MCC H FS 120-2: 1,12 m²

Available models Backloading

Optional accessories

Price rail set

MCC - 2 Hot self serve MCC - 2 Hot self serve

humidified with doors

MCC - 2 Hot full serve humidified







| | Number | Number | Number |
|------------------------------------|---------|----------|---------|
| MCC 60 | | | |
| MCC 60 2 level drop-in | 9389311 | 9389337 | 9389331 |
| MCC 60 2 level drop-in solid back | 9389312 | 9389338* | |
| MCC 90 | | | |
| MCC 90 2 level drop-in | 9389313 | 9389339 | 9389333 |
| MCC 90 2 level drop-in solid back | 9389314 | 9389340* | |
| MCC 120 | | | |
| MCC 120 2 level drop-in | 9389315 | 9389341 | 9389335 |
| MCC 120 2 level drop-in solid back | 9389316 | 9389342* | |

* can only be connected to an external water supply

| Dimensions MCC | | | |
|------------------------------|-----------|-----------|-----------|
| | C00 | C00 mm | C00 |
| Width MCC 60 | 600 mm | 600 mm | 600 mm |
| Width MCC 90 | 900 mm | 900 mm | 900 mm |
| Width MCC 120 | 1200 mm | 1200 mm | 1200 mm |
| Depth | 750 mm | 750 mm | 750 mm |
| Height drop-in total | 733 mm | 733 mm | 733 mm |
| Height drop-in above worktop | 520 mm | 520 mm | 520 mm |
| | | | |
| Technical data MCC | | | |
| Power MCC 60 | 1,36 kW | 1,72 kW | 1,72 kW |
| Power MCC 90 | 2,04 kW | 2,09 kW | 2,09 kW |
| Power MCC 120 | 2,73 kW | 2,79 kW | 2,79 kW |
| Voltage | 1N~ 230 V | 1N~ 230 V | 1N~ 230 V |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |

| Accessories* | MCC Hot self serve | MCC Hot self serve humidified with doors | MCC full serve humidified |
|----------------------------------|--------------------|---|------------------------------|
| Description | Number | Number | Number |
| Price rail set MCC 60 - 2 level | 9389807 | 9389815 | 9389815 |
| Price rail set MCC 90 - 2 level | 9389808 | 9389816 | 9389816 |
| Price rail set MCC 120 - 2 level | 9389809 | 9389817 | 9389817 |
| Front door set MCC 60 - 2 level | 9389835 | | |
| Front door set MCC 90 - 2 level | 9389836 | | |
| Front door set MCC 120 - 2 level | 9389837 | | |

*See page 55 for Merchandising accessories Hot self serve models.

Convenience Counters 3 & 4 level - Hot

Increases food-to-go sales: excellent product presentation Modular design: easy to install, adapt to any store format Space-saving: ideal for areas with limited floor space

Flexibility: available in various widths and as drop-in version or with underframe.

Food safety, longer shelf life: superior holding technology



Features

- 3 level heated open self-serve display cabinet
- Designed for packaged products
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable angle
- Patented Hot Blanket holding technology
- Energy saving hot air recirculation technology
- Total display area:
 - MCC H SS 60-3: 0,72 m²
 - MCC H SS 90-3: 1,15 m²
- MCC H SS 120-3: 1,58 m²

Available models

- Backloading
- Solid back (control panel customer side)

Optional accessories

- Castor set
- Bumper set
- Price rail set
- Front door set
- Merchandising accessories (see page 55)

Modular Convenience Counter self serve humidified with doors

Modular Convenience Counter self serve (3 level only)

Features

- 3 or 4 level heated self-serve display cabinet with front doors
- Humidified to maintain the quality of unpackaged products
- Manual water fill (backloading version only) or automatic water fill
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable angle and height
- Energy saving hot air recirculation technology
- Total display area:
 - MCC H SS FD 60-3: 0,75 $m^2 \ \ MCC$ H SS FD 60-4: 1,00 m^2
 - MCC H SS FD 90-3: 1,20 m² MCC H SS FD 90-4: 1,60 m²
 - MCC H SS FD 120-3: 1,66 m² MCC H SS FD 120-4: 2,19 m²

Modular Convenience Counter full serve humidified

Features

- 3 or 4 level heated full serve display cabinet Humidified to maintain the quality of
- unpackaged products Manual or automatic water fill
- 600, 900, or 1200 mm wide Soft closing sliding doors on operator side
- Slim shelves with adjustable angle and height .
- Energy saving hot air recirculation technology .
- Total display area:
 - MCC H FS 60-3: 0,75 m²
 - MCC H FS 60-4: 1,00 m² - MCC H FS 90-4: 1,60 m² MCC H FS 90-3: 1,20 m²
 - MCC H FS 120-3: 1,66 m² MCC H FS 120-4: 2,19 m²



- Available models
 - Backloading
 - Solid back (control panel customer side)*
 - *Can only be connected to an external water supply

Optional accessories

- Castor set
- Bumper set
- Price rail set

Available models

Backloading

Optional accessories

- Castor set Bumper set
- Price rail set

| NumberNumberNumberMumberNumberNumberMCC 60938001938003MCC 60 level with stand93800119380037MCC 60 level with stand93800129389038'MCC 60 level with stand93800129389038'MCC 60 level with stand93800129389038'MCC 60 level with stand93890149389038'MCC 60 level with stand93890139389039'MCC 90 level with stand93890149389039'MCC 90 level with stand93890149389039'MCC 90 level with stand93890149389039'MCC 90 level with stand solid back93890149389039'MCC 102 level with stand solid back93890159389041'MCC 120 level with stand solid back93890169389042'MCC 120 level with stand93990169389042'MCC 120 level with stand9390169389042'MCC 120 level with stand9390169389042'MCC 120 level with stand9389159389041MCC 120 level with stand9389159389041'MCC 120 level with stand938915938942'MCC 120 level with stand938915938942'MCC 120 level with stand938916'938916'MCC 120 level wi | | MCC Hot self serve | MCC Hot self serve humidified with doors | MCC Hot full serve humidified |
|--|---------------------------------------|---------------------------------------|---|----------------------------------|
| MCC 60 Image: mark stand 9389011 9389037 9389031 MCC 60 3 level with stand solid back 9389012 9389038* Image: mark stand solid back 9389031 MCC 60 4 level with stand solid back 9389012 9389038* Image: mark stand solid back 9389434 9389431 MCC 60 4 level with stand solid back 9389013 9389039 9389033 Image: mark stand solid back Image: mark stand solid back 9389040* Image: mark stand solid back Image: mark stand stand stand stand stand solid back Image: mark stand st | | | | |
| MCC 60 3 level with stand 9389011 9389037 9389031 MCC 60 3 level with stand solid back 9389012 9389038* MCC 60 4 level with stand 9389032 9389038* MCC 60 4 level with stand solid back 9389039 9389431 MCC 90 MCC 90 3 level with stand 9389013 9389039 9389033 MCC 90 3 level with stand 9389014 9389040* MCC 90 4 level with stand 9389014 9389439 9389433 MCC 90 4 level with stand 9389015 9389040* MCC 120 9389015 9389041 9389035 MCC 120 a level with stand 9389015 9389042* MCC 120 4 level with stand solid back 9389042 MCC 120 4 level with stand solid back 9389041 9389042* MCC 120 4 level with stand solid back 9389042* MCC 120 4 level with stand sol | | Number | Number | Number |
| MCC 60 3 level with stand solid back 9389012 9389038* 9389431 MCC 60 4 level with stand 9389434 9389431 MCC 90 9389438* 9389039 MCC 90 3 level with stand 9389013 9389039 9389033 MCC 90 3 level with stand 9389014 9389040* 0 MCC 90 4 level with stand solid back 9389014 9389439 9389433 MCC 90 4 level with stand solid back 9389014 938940* 0 MCC 120 MCC 120 9389015 9389040* 0 MCC 120 a level with stand solid back 9389015 9389042* 0 0 MCC 120 4 level with stand solid back 9389016 9389431 9389435 0 MCC 120 4 level with stand solid back 9389016 938942* 0 0 MCC 120 4 level with stand 9389017 9389431 9389435 0 MCC 120 4 level with stand solid back 9389016 9389042* 0 0 MCC 120 4 level with stand 9389017 9389431 9389435 0 0 | MCC 60 | | | |
| MCC 60 4 level with stand 9389434 9389431 MCC 60 4 level with stand solid back 9389438* MCC 90 MCC 90 3 level with stand 9389013 9389039 9389033 MCC 90 3 level with stand solid back 9389014 9389040* MCC 90 4 level with stand solid back 9389014 9389439 9389433 MCC 90 4 level with stand solid back 938914 9389440* MCC 120 MCC 120 3 level with stand solid back 9389015 9389041 9389035 MCC 120 3 level with stand 9389016 9389042* MCC 120 4 level with stand 9389016 9389434 MCC 120 4 level with stand 9389016 9389442* MCC 120 4 level with stand 9389016 9389442* MCC 120 4 level with stand 9389016 9389442* MCC 100 MMCC 60 / MCC 90 / MCC 120 | MCC 60 3 level with stand | 9389011 | 9389037 | 9389031 |
| MCC 60 4 level with stand solid back 938913 9389039 9389033 MCC 90 9389013 9389039 9389033 MCC 90 3 level with stand 9389014 9389040* Image: Comparison of the stand solid back MCC 90 4 level with stand 9389014 9389040* Image: Comparison of the stand solid back 9389040* MCC 90 4 level with stand 9389016 9389440* Image: Comparison of the stand solid back 9389015 9389042* MCC 120 a level with stand solid back 9389016 938941 9389435 Image: Comparison of the stand solid back 9389016 938942* Image: Comparison of the connected to an external water suppit MCC 120 a level with stand solid back 9389016 9389442* Image: Comparison of the connected to an external water suppit MCC 120 4 level with stand solid back 9389016 9389442* Image: Comparison of the compar | MCC 60 3 level with stand solid back | 9389012 | 9389038* | |
| MCC 90 Image: mode of the stand 9389013 9389039 9389033 MCC 90 3 level with stand 9389014 9389040* Image: mode of the stand Image | MCC 60 4 level with stand | | 9389434 | 9389431 |
| MCC 90 3 level with stand 9389013 9389039 9389033 MCC 90 3 level with stand solid back 9389014 9389040* . MCC 90 4 level with stand 9389014 9389439 9389433 MCC 90 4 level with stand 9389016 9389040* . MCC 120 3 level with stand 9389015 9389041 9389035 MCC 120 3 level with stand 9389016 9389042* . MCC 120 4 level with stand solid back 9389016 9389442* . MCC 120 4 level with stand solid back 9389016 9389442* . MCC 120 4 level with stand solid back 9389016 9389442* . MCC 120 4 level with stand solid back 9389016 9389442* . MCC 120 4 level with stand solid back 938942* . . MCC 120 4 level with stand solid back 060 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm . MCC 120 4 level with stand solid back 060 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm . Dimensions MCC Motth | MCC 60 4 level with stand solid back | | 9389438* | |
| MCC 90 3 level with stand solid back 9389014 9389040* MCC 90 4 level with stand 9389439 9389433 MCC 90 4 level with stand solid back 9389440* MCC 120 MCC 120 3 level with stand 9389015 9389041 9389035 MCC 120 3 level with stand solid back 9389016 9389042* MCC 120 4 level with stand solid back 9389016 9389442* MCC 120 4 level with stand solid back 9389016 9389442* MCC 120 4 level with stand solid back 938900 mm / 1200 mm 9389442* MCC 120 4 level with stand solid back 938900 mm / 1200 mm 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Dimensions MCC Width MCC 60 / MCC 90 / MCC 120 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Depth 750 mm 750 mm 750 mm 1420 mm Height on stand 1420 mm 1420 mm 1420 mm Power MCC 60 2,1 kW | MCC 90 | | | |
| MCC 90 4 level with stand 9389439 9389433 MCC 90 4 level with stand solid back 938940* MCC 120 MCC 120 3 level with stand 9389015 9389041 9389035 MCC 120 3 level with stand 9389016 9389042* MCC 120 4 level with stand 9389016 9389441 9389435 MCC 120 4 level with stand 9389016 9389442* MCC 120 4 level with stand solid back 9389016 9389442* MCC 120 4 level with stand 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Dimensions MCC Width MCC 60 / MCC 90 / MCC 120 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Depth 750 mm 750 mm 750 mm 750 mm Power MCC 60 2,1 kW 1,72 kW 1,72 kW Power MCC 60 3,01 kW 2,09 kW 2,09 kW Power MCC 90 3,01 kW 2,79 kW 2,79 kW </td <td></td> <td></td> <td>9389039</td> <td>9389033</td> | | | 9389039 | 9389033 |
| MCC 90 4 level with stand solid back 9389440* Intervention MCC 120 Image: Mode with stand 9389015 9389041 9389035 MCC 120 3 level with stand 9389016 9389042* Image: Mode with stand 9389042* MCC 120 4 level with stand solid back 9389016 9389442* Image: Mode with stand 9389435 MCC 120 4 level with stand solid back Image: Mode with stand solid back 9389442* Image: Mode with stand solid back MCC 60 / NCC 90 / MCC 120 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Dimensions MCC Image: Mode with Mod | | 9389014 | 9389040* | |
| MCC 120 Image: MCC 120 3 level with stand 9389015 9389041 9389035 MCC 120 3 level with stand solid back 9389016 9389042* Image: MCC 120 4 level with stand solid back 9389016 9389042* Image: MCC 120 4 level with stand solid back 9389441 9389435 MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 4 level with stand solid back Image: MCC 120 0 mC 120 Image: MCC 120 mC 120 mC 120 Image: MCC 120 mC 120 mC 120 Image: MCC 120 mC 120 mC 120 mC 120 mC 120 | MCC 90 4 level with stand | | 9389439 | 9389433 |
| MCC 120 3 level with stand 9389015 9389041 9389035 MCC 120 3 level with stand solid back 9389016 9389042* MCC 120 4 level with stand 9389016 9389441 9389435 MCC 120 4 level with stand 9389042* 9389442* MCC 120 4 level with stand solid back 9389442* Dimensions MCC * can only be connected to an external water supply Width MCC 60 / MCC 90 / MCC 120 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Depth 750 mm 750 mm 750 mm Depth 750 mm 1420 mm 1420 mm Height on stand 1420 mm 1420 mm 1420 mm Power MCC 60 2,1 kW 1,72 kW 1,72 kW Power MCC 90 3,01 kW 2,09 kW 2,09 kW Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | MCC 90 4 level with stand solid back | | 9389440* | |
| MCC 120 3 level with stand solid back 9389016 9389042* MCC 120 4 level with stand 9389040 9389441 9389435 MCC 120 4 level with stand solid back 9389442* MCC 120 4 level with stand solid back 9389442* Dimensions MCC * can only be connected to an external water supply Dimensions MCC 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Depth 750 mm 750 mm 750 mm 750 mm Depth 750 mm 1420 mm 1420 mm 1420 mm Height on stand 1420 mm 1420 mm 1420 mm 1420 mm Power MCC 60 2,1 kW 1,72 kW 1,72 kW 2,09 kW 2,09 kW 2,09 kW 2,09 kW 2,09 kW 2,09 kW 2,79 kW 2,79 kW 2,79 kW 2,79 kW 2,79 kW 1,72 stort 1N- 230 V | MCC 120 | | | |
| MCC 120 4 level with stand 9389441 9389435 MCC 120 4 level with stand solid back 9389442* 9389442* MCC 120 4 level with stand solid back 9389442* 9389442* Dimensions MCC * can only be connected to an external water supply 9389442* Dimensions MCC 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Width MCC 60 / MCC 90 / MCC 120 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Depth 750 mm 750 mm 750 mm Depth 750 mm 1420 mm 1420 mm Height on stand 1420 mm 1420 mm 1420 mm Power MCC 60 2,1 kW 1,72 kW 1,72 kW Power MCC 90 3,01 kW 2,09 kW 2,09 kW Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | MCC 120 3 level with stand | 9389015 | 9389041 | 9389035 |
| MCC 120 4 level with stand solid back 9389442* Image: Calculation of the connected to an external water supply Dimensions MCC <a an="" be="" connected="" external="" nonly="" supply<="" td="" to="" water=""> Image: Calculation of the connected to an external water supply Width MCC 60 / MCC 90 / MCC 120 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Depth 750 mm 750 mm 750 mm Depth 750 mm 750 mm 750 mm Height on stand 1420 mm 1420 mm 1420 mm Power MCC 60 2,1 kW 1,72 kW 1,72 kW Power MCC 90 3,01 kW 2,09 kW 2,09 kW Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | MCC 120 3 level with stand solid back | 9389016 | 9389042* | |
| Image: Constraint of the second section of | MCC 120 4 level with stand | | 9389441 | 9389435 |
| Dimensions MCC 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Width MCC 60 / MCC 90 / MCC 120 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Depth 750 mm 750 mm 750 mm Height on stand 1420 mm 1420 mm 1420 mm Technical data MCC Power MCC 60 2,1 kW 1,72 kW 1,72 kW Power MCC 90 3,01 kW 2,09 kW 2,09 kW Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | MCC 120 4 level with stand solid back | | 9389442* | |
| Width MCC 60 / MCC 90 / MCC 120 600 mm / 900 mm / 1200 mm 600 mm / 900 mm / 1200 mm Depth 750 mm 750 mm 750 mm Height on stand 1420 mm 1420 mm 1420 mm Technical data MCC 2,1 kW 1,72 kW 1,72 kW Power MCC 60 2,1 kW 1,72 kW 2,09 kW Power MCC 90 3,01 kW 2,79 kW 2,79 kW Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | | | * can only be connected to an external water supply | |
| Depth 750 mm 750 mm 750 mm Height on stand 1420 mm 1420 mm 1420 mm Technical data MCC Power MCC 60 2,1 kW 1,72 kW 1,72 kW Power MCC 90 3,01 kW 2,09 kW 2,09 kW Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | Dimensions MCC | | | |
| Height on stand 1420 mm 1420 mm 1420 mm Technical data MCC 1420 mm 1420 mm Power MCC 60 2,1 kW 1,72 kW 1,72 kW 1,72 kW 1,72 kW 1,72 kW 1,72 kW 2,09 kW 2,79 kW 2,00 kW 2,00 kW 2,00 kW 2,00 kW 2,00 kW 2,79 kW 2,79 kW 2,79 kW 2,79 kW 2,79 kW 2,79 kW 2,00 kW | Width MCC 60 / MCC 90 / MCC 120 | 600 mm / 900 mm / 1200 mm | 600 mm / 900 mm / 1200 mm | 600 mm / 900 mm / 1200 mm |
| Technical data MCC Control Contro Control Control | Depth | 750 mm | 750 mm | 750 mm |
| Power MCC 60 2,1 kW 1,72 kW 1,72 kW Power MCC 90 3,01 kW 2,09 kW 2,09 kW Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | Height on stand | 1420 mm | 1420 mm | 1420 mm |
| Power MCC 60 2,1 kW 1,72 kW 1,72 kW Power MCC 90 3,01 kW 2,09 kW 2,09 kW Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | | | | |
| Power MCC 90 3,01 kW 2,09 kW 2,09 kW Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | | 2,1 kW | 1,72 kW | 1,72 kW |
| Power MCC 120 4,01 kW 2,79 kW 2,79 kW Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V 1N~ 230 V | | | | |
| Voltage MCC 60 & MCC 90 1N~ 230 V 1N~ 230 V | | · · · · · · · · · · · · · · · · · · · | | |
| | | | | |
| Voltage Nice 120 V IIV~ 250 V IIV~ 250 V | | | | |
| Frequency 50/60 Hz 50/60 Hz 50/60 Hz | | | | |

| Accessories* | MCC Hot self serve | MCC Hot self serve humidified with doors | MCC full serve humidified |
|---------------------------------------|--------------------|---|------------------------------|
| Description | Number | Number | Number |
| Price rail set MCC 60 - 3 level | 9389801 | 9389811 | 9389811 |
| Price rail set MCC 90 - 3 level | 9389802 | 9389812 | 9389812 |
| Price rail set MCC 120 - 3 level | 9389803 | 9389813 | 9389813 |
| Bumper MCC 60 | 9380206 | 9380206 | 9380206 |
| Bumper MCC 90 | 9380207 | 9380207 | 9380207 |
| Bumper MCC 120 | 9380205 | 9380205 | 9380205 |
| Back 2 Back kit MCC 60 | 9380221 | 9380221 | |
| Back 2 Back kit MCC 90 | 9380209 | 9380209 | |
| Back 2 Back kit MCC 120 | 9380219 | 9380219 | |
| Castor Set (total height MCC + 23 mm) | 9389851 | 9389851 | 9389851 |
| Front door set MCC 60 | 9389831 | | |
| Front door set MCC 90 | 9389832 | | |
| Front door set MCC 120 | 9389833 | | |

*See page 55 for Merchandising accessories Hot self serve models.

Fri-Jado Catalogue Cooking and Counters (valid from 01-01-2022 until further notice). Catalogue is subject to change without notice.

Convenience Counters 3 & 4 level - Hot drop-in

Increases food-to-go sales: excellent product presentation Modular design: easy to install, adapt to any store format Customizable: Easy to build in

Flexibility: available in various widths and as drop-in version or with underframe.

Food safety, longer shelf life: superior holding technology



Modular Convenience Counter self serve drop-in (3 levels only)

Features

- 3 level heated open self-serve display cabinet
- Designed for packaged products
- 600, 900 or 1200 mm wide
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable angle
- Patented Hot Blanket holding technology
- Energy saving hot air recirculation technology
- Total display area:
 - MCC H SS 60-3: 0,72 m²
 - MCC H SS 90-3: 1,15 m²
 - MCC H SS 120-3: 1,58 m²

Available models

- Backloading
- Solid back (control panel customer side)

Optional accessories

- Price rail set
- Front door set
- Merchandising accessories (see page 55)

Modular Convenience Counter self serve humidified with doors drop-in

Features

- 3 or 4 level heated self-serve display cabinet with front doors
- Humidified to maintain the quality of unpackaged products
- Manual water fill (backloading version only) or automatic water fill
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable angle and height
- Energy saving hot air recirculation technology
- Total display area:

- Available models Backloading
- Solid back (control panel customer side)*
- *Can only be connected to an external water supply

Optional accessories

Price rail set



Modular Convenience Counter full serve humidified drop-in

- MCC H SS FD 60-3: 0,75 m² - MCC H SS FD 60-4: 1,00 m² - MCC H SS FD 90-3: 1,20 m² - MCC H SS FD 90-4: 1,60 m² - MCC H SS FD 120-3: 1,66 m² - MCC H SS FD 120-4: 2,19 m²

Features

- 3 or 4 level heated full serve display cabinet
- Humidified to maintain the quality of
- unpackaged products
- Manual or automatic water fill
- 600, 900, or 1200 mm wide
- Soft closing sliding doors on operator side
- Slim shelves with adjustable angle and height
- Energy saving hot air recirculation technology
- Total display area:
- MCC H FS 60-3: 0,75 m²
- MCC H FS 90-3: 1.20 m² - MCC H FS 90-4: 1,60 m²
- MCC H FS 120-4: 2,19 m² - MCC H FS 120-3: 1,66 m²

- Available models Backloading

Optional accessories



52

- - Price rail set

- MCC H FS 60-4: 1,00 m²

| | MCC Hot self serve drop-in | MCC Hot self serve drop-in humidified with doors | MCC Hot full serve drop-in humidified |
|------------------------------------|-------------------------------|---|--|
| | | | |
| | Number | Number | Number |
| MCC 60 | | | |
| MCC 60 3 level drop-in | 9389111 | 9389137 | 9389131 |
| MCC 60 3 level drop-in solid back | 9389112 | 9389138* | |
| MCC 60 4 level drop-in | | 9389537 | 9389531 |
| MCC 60 4 level drop-in solid back | | 9389538* | |
| MCC 90 | | | |
| MCC 90 3 level drop-in | 9389113 | 9389139 | 9389133 |
| MCC 90 3 level drop-in solid back | 9389114 | 9389140* | |
| MCC 90 4 level drop-in | | 9389539 | 9389533 |
| MCC 90 4 level drop-in solid back | | 9389540* | |
| MCC 120 | | | |
| MCC 120 3 level drop-in | 9389115 | 9389141 | 9389135 |
| MCC 120 3 level drop-in solid back | 9389116 | 9389142* | |
| MCC 120 4 level drop-in | | 9389541 | 9389535 |
| MCC 120 4 level drop-in solid back | | 9389542* | |
| | | * can only be connected to an external water supply | |
| Dimensions MCC drop-in | | | |
| Width MCC 60 | 600 mm | 600 mm | 600 mm |
| Width MCC 90 | 900 mm | 900 mm | 900 mm |
| Width MCC 120 | 1200 mm | 1200 mm | 1200 mm |
| Depth | 750 mm | 750 mm | 750 mm |
| Height drop-in total | 1053 mm | 1053 mm | 1053 mm |
| Height drop-in above worktop | 840 mm | 840 mm | 840 mm |
| | | | |
| Technical data MCC | | | |
| Power MCC 60 | 2,01 kW | 1,72 kW | 1,72 kW |
| Power MCC 90 | 3,01 kW | 2,09 kW | 2,09 kW |
| Power MCC 120 | 4,01 kW | 2,79 kW | 2,79 kW |
| Voltage MCC 60 | 1N~ 230 V | 1N~ 230 V | 1N~ 230 V |
| Voltage MCC 90 | 1N~ 230 V | 1N~ 230 V | 1N~ 230 V |
| | | | |
| Voltage MCC 120 | 3N~ 400/230 V | 1N~ 230 V | 1N~ 230 V |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |

| Accessories* | MCC Hot self serve drop-in | MCC Hot self serve drop-in humidified with doors | MCC Hot full serve drop-in humidified |
|----------------------------------|-------------------------------|---|--|
| Description | Number | Number | Number |
| Price rail set MCC 60 - 3 level | 9389801 | 9389811 | 9389811 |
| Price rail set MCC 90 - 3 level | 9389802 | 9389812 | 9389812 |
| Price rail set MCC 120 - 3 level | 9389803 | 9389813 | 9389813 |
| Front door set MCC 60 | 9389831 | | |
| Front door set MCC 90 | 9389832 | | |
| Front door set MCC 120 | 9389833 | | |

*See page 55 for Merchandising accessories Hot self serve models.



Accessories MCC Hot self-serve - For packaged hot food

Fri-Jado created a range of high-quality interchangeable and compatible accessories to take food visibility and layout in its hot MDD and MCC self-serve units to the next level. These accessories are developed with packaged hot food in mind.

Condiment holder

The condiment holder can be used for cross selling or dispensing items such as napkins, bags or cutlery. Four dividers are provided which can be placed at various positions to create separate compartments. The condiment holder hooks to the raised glass edge at the front, which can be found on all MDD units and all MCC self-serve units with open front.

Merchandising racks

Merchandising racks can be used to angle products towards the customer for optimal visual impact and will increase the capacity of your counter. The rack will fit products up to 5 cm deep. Although racks can be used separately we recommended a shelf tray to fixate the position on your shelve. There are three sizes available to suit the different shelf depths.

Shelf dividers

Shelf Dividers can be used to to separate different products and highlight a clear divide between offers. Dividers can only be used in combination with a shelf tray. There are three sizes available to suit the different shelf depths.

Shelf insert trays

Shelf insert trays can be used to organize your products on a convenient location away from your counter. They also allow the positioning of dividers and merchandising racks in a most favorable way. Different sizes are available depending on unit width and shelf depth. On each MDD and MCC shelf, two insert trays will fit side by side. Please use the table below to select the required article.

Accessories **MCC Hot self-serve** Description Compatibility Number Condiment holder - only for self serve MCC 60/90/120 9380198 Merchandising rack 410 mm - top shelf MCC 60/90/120 9384463 Merchandising rack 475 mm - middle shelf MCC 60/90/120 9384473 Merchandising rack 550 mm- bottom shelf MCC 60/90/120 9384475 Shelf divider 410 mm - top shelf MCC 60/90/120 9384504 Shelf divider 475 mm - middle shelf MCC 60/90/120 9384503 MCC 60/90/120 Shelf divider 550 mm - bottom shelf 9384505 Shelf insert 250x410mm - top shelf MCC 60 9384534 Shelf insert tray 250x475mm - middle shelf MCC 60 9384535 Shelf insert tray 250x550mm - bottom shelf MCC 60 9384536 Shelf insert tray 400x410mm - top shelf MCC 90 9384461 Shelf insert tray 400x475mm - middle shelf 9384470 MCC 90 Shelf insert tray 400x550mm - bottom shelf MCC 90 9384471 Shelf insert tray 550x410mm - top shelf MCC 120 9384537 Shelf insert tray 550x475mm - middle shelf MCC 120 9384538 Shelf insert tray 550x550mm - bottom shelf MCC 120 9384539











Convenience Counters 2 levels - Cold

Increases food-to-go sales: excellent product presentation Modular design: easy to install, adapt to any store format Space-saving: ideal for areas with limited floor space **Flexibility**: available in various widths and as drop-in model or with underframe.

Food safety, longer shelf life: superior holding technology

Modular Convenience Counter self serve (available from 1 May 2022)



Features

- 2 level refrigerated open self-serve display cabinet
- Designed for packaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable height and angle
- Mounting set for price rail on shelf
- Patented air guiding technology
- Top performer in energy efficiency based on R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
- MCC C SS 90-2: 0,80 m^2
- MCC C SS 120-2: 1,10 m²
- MCC C SS 150-2: 1,40 m²

Available modelsBackloading

- Solid back (control panel customer side)
- **Optional accessories**
- Castor set
- Bumper set
- Evaporation tray

Modular Convenience Counter self serve with doors (available from 1 May 2022)



- Features
- 2level refrigerated self-serve display cabinet with front doors
- Designed for packaged and unpackaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on shelve
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable height and angle
- Mounting set for price rail on each shelf
- Patented air guiding technology
- Top performer in energy efficiency based on R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
- MCC C SS FD 90-2: 0,80 m²
- MCC C SS FD 120-2: 1,10 m²
- MCC C SS FD 150-2: 1,40 m²

Available models

- Backloading
- Solid back (control panel customer side)

Optional accessories

- Castor set
- Bumper set
- Evaporation tray

Modular Convenience Counter full serve (available from 1 May 2022)



Features

- 2level refrigerated full serve display cabinet Designed for packaged and unpackaged
- Designed for packaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve
- Soft closing sliding doors on operator side
- Slim shelves with adjustable angle and height
- Top performer in energy efficiency based on R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
 - MCC C FS 90-2: 0,80 m²
 - MCC C FS 120-2: 1,10 m²
 - MCC C FS 150-2: 1,40 m²

Available models

Backloading

Optional accessories

- Castor set
- Bumper set
- Mounting set for price rail
- Evaporation tray

| | MCC Cold self serve | MCC Cold self serve with doors | MCC Cold full serve | |
|---------------------------------------|---------------------|-----------------------------------|---------------------|--|
| | | | | |
| | Number | Number | Number | |
| MCC 90 | | | | |
| MCC 90 2 level with stand | 9389201 | 9389201 + 9389836 | 9389221 | |
| MCC 90 2 level with stand solid back | 9389202 | 9389202 + 9389836 | | |
| MCC 120 | | | | |
| MCC 120 2 level with stand | 9389203 | 9389203 + 9389837 | 9389223 | |
| MCC 120 2 level with stand solid back | 9389204 | 9389204 + 9389837 | | |
| MCC 150 | | | | |
| MCC 150 2 level with stand | 9389205 | 9389205 + 9389838 | 9389225 | |
| MCC 150 2 level with stand solid back | 9389206 | 9389206 + 9389838 | | |
| Dimensions MCC | | | | |
| Width MCC 90 | 900 mm | 900 mm | 900 mm | |
| Width MCC 120 | 1200 mm | 1200 mm | 1200 mm | |
| Width MCC 150 | 1500 mm | 1500 mm | 1500 mm | |
| Depth | 750 mm | 750 mm | 750 mm | |
| Height on stand | 1420 mm | 1420 mm | 1420 mm | |
| Technical data MCC | | | | |
| Power MCC 90 | 0,48 kW | 0,48 kW | 0,40 kW | |
| Power MCC 120 | 0,68 kW | 0,68 kW | 0,48 kW | |
| Power MCC 150 | 0,83 kW | 0,83 kW | 0,71 kW | |
| Voltage MCC 90/120/150 | 1N~ 230 V | 1N~ 230 V | 1N~ 230 V | |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz | |
| | | | | |

| Accessories | MCC Cold self serve MCC Cold self serve with doors | | MCC Cold full serve |
|--|---|---------|---------------------|
| Description | Number | Number | Number |
| Mounting set price rail FS 90-2 level | | | 9389816 |
| Mounting set price rail FS 120-2 level | | | 9389817 |
| Mounting set price rail FS 150-2 level | | | 9389818 |
| Evaporation tray | 9389820 | 9389820 | 9389820 |
| Bumper MCC 90 | 9380207 | 9380207 | 9380207 |
| Bumper MCC 120 | 9380205 | 9380205 | 9380205 |
| Bumper MCC 150 | 9380208 | 9380208 | 9380208 |
| Castor Set (total height MCC + 23 mm) | 9389852 | 9389852 | 9389852 |

Convenience Counters 2 levels - Cold drop-in

Increases food-to-go sales: excellent product presentation Modular design: easy to install, adapt to any store format Space-saving: ideal for areas with limited floor space **Flexibility**: available in various widths and as drop-in model or with underframe

Food safety, longer shelf life: superior holding technology

Modular Convenience Counter self serve drop-in (available from 1 May 2022)



Features

- 2 level refrigerated open self-serve display cabinet
- Designed for packaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable height and angle
- Mounting set for price rail on shelf
- Patented air guiding technology
- Top performer in energy efficiency based on R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
 - MCC C SS 90-2: 0,80 m²
 - MCC C SS 120-2: 1,10 m²
- MCC C SS 150-2: 1,40 m²

Available models Backloading

- Solid back (control panel customer side)
- **Optional accessories**
- Evaporation tray

Modular Convenience Counter self serve with doors drop-in (available from 1 May 2022)



- Features
- 2level refrigerated self-serve display cabinet with front doors
- Designed for packaged and unpackaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable height and angle
- Mounting set for price rail on shelf
- Patented air guiding technology
- Top performer in energy efficiency based on R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
- MCC C SS FD 90-2: 0,80 m²
- MCC C SS FD 120-2: 1,10 m²
- MCC C SS FD 150-2: 1,40 m²

Available models

- Backloading
- Solid back (control panel customer side)

Optional accessories

Evaporation tray

Modular Convenience Counter full serve drop-in (available from 1 May 2022)



Features

- 2level refrigerated full serve display cabinet
- Designed for packaged and unpackaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve
- Soft closing sliding doors on operator side
- Slim shelves with adjustable angle and height
- Top performer in energy efficiency based on R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
 - MCC C FS 90-2: 0,80 m²
 - MCC C FS 120-2: 1,10 m²
 - MCC C FS 150-2: 1,40 m²

Available models

Backloading

Optional accessories

- Mounting set for price rail
- Evaporation tray

| | MCC Cold self serve drop-in | MCC Cold self serve with doors drop-in | MCC Cold full serve drop-in |
|------------------------------------|--------------------------------|---|--------------------------------|
| | | | |
| | Number | Number | Number |
| MCC 90 | | | |
| MCC 90 2 level drop-in | 9389301 | 9389301 + 9389836 | 9389321 |
| MCC 90 2 level drop-in solid back | 9389302 | 9389302 + 9389836 | |
| MCC 120 | | | |
| MCC 120 2 level drop-in | 9389303 | 9389303 + 9389837 | 9389323 |
| MCC 120 2 level drop-in solid back | 9389304 | 9389304 + 9389837 | |
| MCC 150 | | | |
| MCC 150 2 level drop-in | 9389305 | 9389305 + 9389838 | 9389325 |
| MCC 150 2 level drop-in solid back | 9389306 | 9389306 + 9389838 | |
| Dimensions MCC | | | |
| Width MCC 90 | 900 mm | 900 mm | 900 mm |
| Width MCC 120 | 1200 mm | 1200 mm | 1200 mm |
| Width MCC 150 | 1500 mm | 1500 mm | 1500 mm |
| Depth | 750 mm | 750 mm | 750 mm |
| Height drop-in total | 733 mm | 733 mm | 733 mm |
| Height drop-in above worktop | 520 mm | 520 mm | 520 mm |
| Technical data MCC | | | |
| Power MCC 90 | 0,48 kW | 0,48 kW | 0,40 kW |
| Power MCC 120 | 0,68 kW | 0,68 kW | 0,48 kW |
| Power MCC 150 | 0,83 kW | 0,83 kW | 0,71 kW |
| Voltage MCC 90/120/150 | 1N~ 230 V | 1N~ 230 V | 1N~ 230 V |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |

| Accessories | MCC Cold self serve | MCC Cold self serve with doors | MCC Cold full serve |
|--|---------------------|-----------------------------------|---------------------|
| Description | Number | Number | Number |
| Mounting set price rail FS 90-2 level | | | 9389816 |
| Mounting set price rail FS 120-2 level | | | 9389817 |
| Mounting set price rail FS 150-2 level | | | 9389818 |
| Evaporation tray | 9389820 | 9389820 | 9389820 |

Convenience Counters 3 & 4 levels - Cold

Increases food-to-go sales: excellent product presentation Modular design: easy to install, adapt to any store format Space-saving: ideal for areas with limited floor space

Flexibility: available in various widths and as drop-in model or with underframe

Food safety, longer shelf life: superior holding technology

Modular Convenience Counter self serve

Features

- 3 or 4 level refrigerated open self-serve display cabinet
- Designed for packaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable height and angle
- Mounting set for price rail on each shelf
- Patented air guiding technology
- Top performer in energy efficiency based on
- R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
 - MCC C SS 90-3: 1,18 m²
 - MCC C SS 90-4: 1,56 m² MCC C SS 120-3: 1,62 m²
 - MCC C SS 120-4: 2,15 m² MCC C SS 150-3: 2,07 m² - MCC C SS 150-4: 2,73 m²

- Available models
- Backloading • Solid back (control panel customer side)

Optional accessories

- Castor set
- Bumper set
- Evaporation tray



Modular Convenience Counter self serve with doors

Features

- 3 or 4 level refrigerated self-serve display cabinet with front doors
- Designed for packaged and unpackaged products

- Soft closing sliding doors on operator side (backloading version)
- Mounting set for price rail on each shelf
- Patented air guiding technology
- Top performer in energy efficiency based on R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
- MCC C SS FD 90-3: 1,18 m² MCC C SS FD 90-4: 1,56 m²
 - MCC C SS FD 120-3: 1,62 m² MCC C SS FD 120-4: 2,15 m²
- MCC C SS FD 150-3: 2,07 m² MCC C SS FD 150-4: 2,73 m²

Modular Convenience Counter full serve

Features

- 3 or 4 level refrigerated full serve display cabinet
- Designed for packaged and unpackaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve
- Soft closing sliding doors on operator side
- Slim shelves with adjustable angle and height Top performer in energy efficiency based on
- R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
- MCC C FS 90-3: 1,18 m²
- MCC C FS 120-3: 1,62 m²
- MCC C FS 150-3: 2,07 m²

Available models

Backloading

Optional accessories

- Castor set
- Bumper set

- MCC C FS 90-4: 1,56 m² - MCC C FS 120-4: 2,15 m²

- MCC C FS 150-4: 2,73 m²

- Mounting set for price rail
- Evaporation tray



- - **Optional accessories**
 - Castor set
 - Bumper set
 - Evaporation tray
- Available models
 - Backloading
 - Solid back (control panel customer side)

- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve

- Slim shelves with adjustable height and angle

| Energy labels | MCC Cold s | elf serve | serve MCC Cold self serve with doors | | MCC Cold full se | rve |
|---|------------|-----------|--------------------------------------|------------------------|------------------|-----|
| MCC Cold full serve 90 MCC Cold self serve 90 MCC Cold full serve 120 MCCCold full serve 150 MCC Cold self serve 120 MCC Cold self serve 120 | | | | | | |
| | Number | | Number | | Number | |
| MCC 90 | Number | | Number | | Миньег | |
| MCC 90 3 level with stand | 9389001 | | 9389001 + 938983 | 2 | 9389021 | |
| MCC 90 3 level with stand solid back | 9389002 | | 9389002 + 938983 | | 3303021 | |
| MCC 90 4 level with stand | 9389401 | | 9389401 + 938983 | | 9389421 | |
| MCC 90 4 level with stand solid back | 9389402 | | 9389402 + 938983 | | 5505421 | |
| MCC 120 | 5505102 | | | | | |
| MCC 120 3 level with stand | 9389003 | | 9389003 + 938983 | 3 | 9389023 | |
| MCC 120 3 level with stand solid back | | | | | 5505025 | |
| | 9389004 | | 9389004 + 9389833 | | 0200422 | |
| MCC 120 4 level with stand | 9389403 | | 9389403 + 9389833 | | 9389423 | |
| MCC 120 4 level with stand solid back | 9389404 | | 9389404 + 9389833 | | | |
| MCC 150 | | | | | | |
| MCC 150 3 level with stand | 9389005 | | 9389005 + 9389834 | | 9389025 | |
| MCC 150 3 level with stand solid back | 9389006 | | 9389006 + 938983 | 4 | | |
| MCC 150 4 level with stand | 9389405 | | 9389405 + 938983 | 4 | 9389425 | |
| MCC 150 4 level with stand solid back | 9389406 | | 9389406 + 938983 | 4 | | |
| Dimensions MCC | | | | | | |
| Width MCC 90 | 900 | mm | 90 | 0 mm | 900 mm | |
| Width MCC 120 | 1200 | mm | 120 | 0 mm | 1200 mm | |
| Width MCC 150 | 1500 | mm | 1500 mm | | 1500 mm | |
| Depth | 750 | mm | 750 mm | | 750 mm | |
| Height on stand | 1420 | mm | 1420 mm | | 1420 mm | |
| Technical data MCC | | | | | | |
| Power MCC 90 | 0,49 k | | 0,49 kW | | 0,41 kW | |
| Power MCC 120 | 0,70 k | | 0,70 kW | | 0,50 kW | |
| Power MCC 150 | 0,83 kW | | 0,83 kW | | 0,71 kW | |
| Voltage MCC 90/120/150 | 1N~ 230 V | | 1N~ 230 V | | 1N~ 230 V | |
| Frequency | 50 H | Z | 50 | Hz | 50 Hz | |
| Accessories | MCC Cold s | elf serve | | elf serve with oors | MCC Cold full se | rve |
| Description | Number | Price | Number | Price | Number | |
| Mounting set price rail FS 90-3 level | | | | | 9389812 | |
| Mounting set price rail FS 120-3 level | | | | | 9389813 | |

| Mounting set price rall FS 90-3 level | | | 9389812 |
|--|---------|---------|---------|
| Mounting set price rail FS 120-3 level | | | 9389813 |
| Mounting set price rail FS 150-3 level | | | 9389814 |
| Mounting set price rail FS 90-4 level | | | 9389854 |
| Mounting set price rail FS 120-4 level | | | 9389855 |
| Mounting set price rail FS 150-4 level | | | 9389856 |
| Evaporation tray | 9389820 | 9389820 | 9389820 |
| Back 2 Back kit MCC 90 | 9380209 | 9380209 | |
| Back 2 Back kit MCC 120 | 9380219 | 9380219 | |
| Back 2 Back kit MCC 150 | 9380229 | 9380229 | |
| Bumper MCC 90 | 9380207 | 9380207 | 9380207 |
| Bumper MCC 120 | 9380205 | 9380205 | 9380205 |
| Bumper MCC 150 | 9380208 | 9380208 | 9380208 |
| Castor Set (total height MCC + 23 mm) | 9389852 | 9389852 | 9389852 |

Fri-Jado Catalogue Cooking and Counters (valid from 01-01-2022 until further notice). Catalogue is subject to change without notice.

Convenience Counters 3 & 4 levels - Cold drop-in

Increases food-to-go sales: excellent product presentation Modular design: easy to install, adapt to any store format Customizable: Easy to build in

Flexibility: available in various widths and as drop-in model or with underframe

Food safety, longer shelf life: superior holding technology



Modular Convenience Counter self serve drop-in

Features

- 3 or 4 level refrigerated open self-serve display cabinet
- Designed for packaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve Soft closing sliding doors on operator side
- (backloading version)
- Slim shelves with adjustable height and angle
- Patented transparent air guiding technology
- Top performer in energy efficiency based on
- R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
- MCC C SS 90-3: 1,18 m²
- MCC C SS 120-3: 1,62 m²
- MCC C SS 150-3: 2,07 m²

Available models

- Backloading
- Solid back (control panel customer side)

Optional accessories

Evaporation tray

Available models

Optional accessories

Evaporation tray

• Solid back (control panel customer side)

Backloading

Modular Convenience Counter self serve with doors drop-in

- MCC C SS 90-4: 1,56 m²

- MCC C SS 120-4: 2,15 m² - MCC C SS 150-4: 2,73 m²

Features

- 3 or 4 level refrigerated self-serve display cabinet with front doors
- Designed for packaged and unpackaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve
- Soft closing sliding doors on operator side (backloading version)
- Slim shelves with adjustable height and angle
- Patented transparent air guiding technology
- Top performer in energy efficiency based on
- R290 refrigerant
- 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:

- MCC C SS FD 150-3: 2,07 m² MCC C SS FD 150-4: 2,73 m²

Modular Convenience Counter full serve drop-in

Features

- 3 or 4 level refrigerated full serve display cabinet
- Designed for packaged and unpackaged products
- 900, 1200, or 1500 mm wide
- Integrated LED lights on each shelve
- Soft closing sliding doors on operator side
- Slim shelves with adjustable angle and height
- Top performer in energy efficiency based on
- R290 refrigerant 3M1 refrigeration classification
- Lowest possible energy consumption
- Total display area:
- MCC C FS 90-3: 1,18 m²
- MCC C FS 120-3: 1,62 m² _
- _ MCC C FS 150-3: 2,07 m²

Available models

Backloading

Optional accessories


- Price rail set
- Evaporation tray

- MCC C FS 90-4: 1,56 m²

MCC C FS 120-4: 2,15 m²

- MCC C FS 150-4: 2,73 m²





| Energy labels | MCC Cold self serve drop-in | ICC Cold self serve drop-in MCC Cold self serve with doors drop-in | |
|--|-----------------------------|--|-----------|
| MCC Cold full serve 90 MCC Cold self serve 90 MCC Cold full serve 120 MCCCold full serve 150 MCC Cold self serve 120 MCC Cold self serve 120 MCC Cold self serve 150 | | | |
| | Number | Number | Number |
| MCC 90 | | | |
| MCC 90 3 level drop-in | 9389101 | 9389101 + 9389832 | 9389121 |
| MCC 90 3 level drop-in solid back | 9389102 | 9389102 + 9389832 | |
| MCC 90 4 level drop-in | 9389501 | 9389501 + 9389832 | 9389521 |
| MCC 90 4 level drop-in solid back | 9389502 | 9389502 + 9389832 | 5565521 |
| MCC 120 | 3363302 | 3303502 + 3303032 | |
| MCC 120 3 level drop-in | 9389103 | 9389103 + 9389833 | 9389123 |
| MCC 120 3 level drop-in solid back | 9389104 | 9389104 + 9389833 | 5565125 |
| MCC 120 4 level drop-in | 9389503 | 9389503 + 9389833 | 9389523 |
| MCC 120 4 level drop-in solid back | 9389504 | 9389504 + 9389833 | 5565325 |
| MCC 150 | | | |
| MCC 150 3 level drop-in | 9389105 | 9389105 + 9389834 | 9389125 |
| MCC 150 3 level drop-in solid back | | 9389106 + 9389834 | 3363125 |
| · . | 9389106 | | 0000505 |
| MCC 150 4 level drop-in | 9389505 | 9389505 + 9389834 | 9389525 |
| MCC 150 4 level drop-in solid back | 9389506 | 9389506 + 9389834 | |
| Dimensions MCC drop-in | | | |
| Width MCC 90 | 900 mm | 900 mm | 900 mm |
| Width MCC 120 | 1200 mm | 1200 mm | 1200 mm |
| Width MCC 150 | 1500 mm | 1500 mm | 1500 mm |
| Depth | 750 mm | 750 mm | 750 mm |
| Height drop-in total | 1053 mm | 1053 mm | 1053 mm |
| Height drop-in above worktop | 840 mm | | |
| Technical data MCC | | | |
| Power MCC 90 | 0,49 kW | 0,49 kW | 0,41 kW |
| Power MCC 120 | 0,70kW | 0,70 kW | 0,50 kW |
| Power MCC 150 | 0,83 kW | 0,83 kW | 0,71 kW |
| Voltage MCC 90/120/150 | 1N~ 230 V | 1N~ 230 V | 1N~ 230 V |
| Frequency | 50 Hz | 50 Hz | 50 Hz |

| Accessories | MCC Cold self serve drop-in | MCC Cold self serve with doors drop-in | MCC Cold full serve drop-in |
|--|-----------------------------|---|--------------------------------|
| Description | Number | Number | Number |
| Mounting set price rail FS 90-3 level | | | 9389812 |
| Mounting set price rail FS 120-3 level | | | 9389813 |
| Mounting set price rail FS 150-3 level | | | 9389814 |
| Mounting set price rail FS 90-4 level | | | 9389854 |
| Mounting set price rail FS 120-4 level | | | 9389855 |
| Mounting set price rail FS 150-4 level | | | 9389856 |
| Evaporation tray | 9389820 | 9389820 | 9389820 |

| Notes |
|-------|
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

| Notes |
|-------|
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

Prices

All prices are in Euros, excluding VAT and other governmental levies payable at removal, sale and delivery. Fri-Jado reserves the right to alter prices without notice.

Disclaimer

Whilst every care has been taken in the compilation of this price list, and every attempt has been made to present up-to-date and accurate information, we cannot guarantee that inaccuracies will not occur. Fri-Jado cannot be held responsible for any loss, damage or inconvenience caused as a result of any inaccuracy or error within this price list.

All our agreements, quotations, deliveries, etc. are subject to our company's General terms and conditions of sale and delivery, filed with the clerk of the District Court in Breda, The Netherlands under no. 35/1999. These terms and conditions can be downloaded from www.frijado.com.



making food irresistible

www.frijado.com