

Vitrine Coolers



VK33-200-I

Vitrine Cooler GN1/4

- Stainless steel
- Accepts GN1/4 pans (Not supplied)
- Static cooling
- Glass structure for protection of food
- Adjustable feet



Glass structure for protection
of food



Stainless steel lid as option



VK33-120-I Vitrine Cooler GN1/4

- Stainless steel
- Accepts GN1/4 pans (Not supplied)
- Static cooling
- Glass structure for protection of food
- Adjustable feet

VK33-160-I Vitrine Cooler GN1/4

- Stainless steel
- Accepts GN1/4 pans (Not supplied)
- Static cooling
- Glass structure for protection of food
- Adjustable feet

MODEL		VK33-120-I	VK33-140 I	VK33-150-I	VK33-160-I	VK33-180-I	VK33-200-I
Gross / Net Volume	l	32 / 32	40 / 40	44 / 44	48 / 48	55 / 55	63 / 63
Gross / Net Weight	kg	45 / 40	48 / 43	50 / 45	55 / 50	58 / 53	63 / 58
Climate Class		4	4	4	4	4	4
Temperature Range	°C	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10
Lid Number & Type		-	-	-	-	-	-
Number of dividers	pcs	5	6	7	7	8	10
Feet / Legs		4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Exterior Finish		SS304	SS304	SS304	SS304	SS304	SS304
Interior Finish		SS304	SS304	SS304	SS304	SS304	SS304
Thermometer		Yes	Yes	Yes	Yes	Yes	Yes
Type of Controller		Electronic	Electronic	Electronic	Electronic	Electronic	Electronic
Noise Level	db(A)	47	47	47	47	47	47
Type of Cooling		Static	Static	Static	Static	Static	Static
Type of Defrost		Manual	Manual	Manual	Manual	Manual	Manual
Refrigerant		R600a	R600a	R600a	R600a	R600a	R600a
Refrigerant Charge	g	40	40	40	40	40	40
Input Power	W	112	112	112	112	112	112
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/h	0,16	0,16	0,16	0,17	0,18	0,18
Internal Dimension (WxDxH)	mm	845 x 245 x 155	1045 x 245 x 155	1145 x 245 x 155	1245 x 245 x 155	1445 x 245 x 155	1645 x 245 x 155
External Dimension (WxDxH)	mm	1200 x 335 x 225	1400 x 335 x 225	1500 x 335 x 225	1600 x 335 x 225	1800 x 335 x 225	2000 x 335 x 225
Packed Dimension (WxDxH)	mm	1280 x 380 x 310	1480 x 380 x 310	1580 x 380 x 310	1680 x 380 x 310	1880 x 380 x 310	2080 x 380 x 310
40ft Container Load	pcs	250	250	250	250	250	250

Vitrine Coolers



VK33-200-I S/S

Vitrine Cooler GN1/4

- Stainless steel
- Accepts GN1/4 pans (Not supplied)
- Static cooling
- Stainless steel lid
- Adjustable feet



Glass structure as option



Stainless steel lid for protection of food



VK33-120-I S/S

Vitrine Cooler GN1/4

- Stainless steel
- Accepts GN1/4 pans (Not supplied)
- Static cooling
- Stainless steel lid
- Adjustable feet

VK33-150-I S/S

Vitrine Cooler GN1/4

- Stainless steel
- Accepts GN1/4 pans (Not supplied)
- Static cooling
- Stainless steel lid
- Adjustable feet

MODEL		VK33-120-I S/S	VK33-150-I S/S	VK33-180-I S/S	VK33-200-I S/S
Gross / Net Volume	l	32 / 32	44 / 44	55 / 55	63 / 63
Gross / Net Weight	kg	45 / 40	50 / 45	58 / 53	63 / 58
Climate Class		4	4	4	4
Temperature Range	°C	2 to 10	2 to 10	2 to 10	2 to 10
Lid Number & Type		SS304 lid	SS304 lid	SS304 lid	SS304 lid
Number of dividers	pcs	5	7	8	10
Feet / Legs		4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Exterior Finish		SS304	SS304	SS304	SS304
Interior Finish		SS304	SS304	SS304	SS304
Thermometer		Yes	Yes	Yes	Yes
Type of Controller		Electronic	Electronic	Electronic	Electronic
Noise Level	db(A)	47	47	47	47
Type of Cooling		Static	Static	Static	Static
Type of Defrost		Manual	Manual	Manual	Manual
Refrigerant		R600a	R600a	R600a	R600a
Refrigerant Charge	g	40	40	40	40
Input Power	W	112	112	112	112
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/h	0,16	0,16	0,18	0,18
Internal Dimension (WxDxH)	mm	845 x 245 x 155	1145 x 245 x 155	1445 x 245 x 155	1645 x 245 x 155
External Dimension (WxDxH)	mm	1200 x 335 x 260	1500 x 335 x 260	1800 x 335 x 260	2000 x 335 x 260
Packed Dimension (WxDxH)	mm	1280 x 380 x 310	1580 x 380 x 310	1880 x 380 x 310	2080 x 380 x 310
40ft Container Load	pcs	250	250	250	250

Vitrine Coolers



VK38-200-I

Vitrine Cooler GN1/3

- Stainless steel
- Accepts GN1/3 pans (Not supplied)
- Static cooling
- Glass structure for protection of food
- Adjustable feet



Glass structure for protection of food



Stainless steel lid as option



VK38-120-I Vitrine Cooler GN1/3

- Stainless steel
- Accepts GN1/3 pans (Not supplied)
- Static cooling
- Glass structure for protection of food
- Adjustable feet

VK38-150-I Vitrine Cooler GN1/3

- Stainless steel
- Accepts GN1/3 pans (Not supplied)
- Static cooling
- Glass structure for protection of food
- Adjustable feet

MODEL		VK38-120-I	VK38-150-I	VK38-160-I	VK38-180-I	VK38-200-I
Gross / Net Volume	l	40 / 40	54 / 54	59 / 59	69 / 69	78 / 78
Gross / Net Weight	kg	45 / 40	56 / 51	61 / 56	74 / 69	78 / 73
Climate Class		4	4	4	4	4
Temperature Range	°C	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10
Lid Number & Type		-	-	-	-	-
Number of dividers	pcs	7	9	10	10	12
Feet / Legs		4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Exterior Finish		SS304	SS304	SS304	SS304	SS304
Interior Finish		SS304	SS304	SS304	SS304	SS304
Thermometer		Yes	Yes	Yes	Yes	Yes
Type of Controller		Electronic	Electronic	Electronic	Electronic	Electronic
Noise Level	db(A)	47	47	47	47	47
Type of Cooling		Static	Static	Static	Static	Static
Type of Defrost		Manual	Manual	Manual	Manual	Manual
Refrigerant		R600a	R600a	R600a	R600a	R600a
Refrigerant Charge	g	40	40	40	40	40
Input Power	W	112	112	112	112	112
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/h	0,16	0,17	0,18	0,19	0,19
Internal Dimension (WxDxH)	mm	845 x 305 x 155	1145 x 305 x 155	1245 x 305 x 155	1445 x 305 x 155	1645 x 305 x 155
External Dimension (WxDxH)	mm	1200 x 395 x 225	1500 x 395 x 225	1600 x 395 x 225	1800 x 395 x 225	2000 x 395 x 225
Packed Dimension (WxDxH)	mm	1280 x 440 x 310	1580 x 440 x 310	1680 x 440 x 310	1880 x 440 x 310	2080 x 440 x 310
40ft Container Load	pcs	250	250	250	250	250

Vitrine Coolers



VK38-120-I S/S

Vitrine Cooler GN1/3

- Stainless steel
- Accepts GN1/3 pans (Not supplied)
- Static cooling
- Stainless steel lid
- Adjustable feet



Glass structure as option



Stainless steel lid for protection of food



VK38-150-I S/S

Vitrine Cooler GN1/3

- Stainless steel
- Accepts GN1/3 pans (Not supplied)
- Static cooling
- Stainless steel lid
- Adjustable feet

VK38-160-I S/S

Vitrine Cooler GN1/3

- Stainless steel
- Accepts GN1/3 pans (Not supplied)
- Static cooling
- Stainless steel lid
- Adjustable feet

MODEL		VK38-120-I S/S	VK38-150-I S/S	VK38-160-I S/S	VK38-180-I S/S	VK38-200-I S/S
Gross / Net Volume	l	40 / 40	54 / 54	59 / 59	69 / 69	78 / 78
Gross / Net Weight	kg	45 / 40	56 / 51	61 / 56	74 / 69	78 / 73
Climate Class		4	4	4	4	4
Temperature Range	°C	2 to 10	2 to 10	2 to 10	2 to 10	2 to 10
Lid Number & Type		SS304 lid	SS304 lid	SS304 lid	SS304 lid	SS304 lid
Number of dividers	pcs	7	9	10	10	12
Feet / Legs		4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Exterior Finish		SS304	SS304	SS304	SS304	SS304
Interior Finish		SS304	SS304	SS304	SS304	SS304
Thermometer		Yes	Yes	Yes	Yes	Yes
Type of Controller		Electronic	Electronic	Electronic	Electronic	Electronic
Noise Level	db(A)	47	47	47	47	47
Type of Cooling		Static	Static	Static	Static	Static
Type of Defrost		Manual	Manual	Manual	Manual	Manual
Refrigerant		R600a	R600a	R600a	R600a	R600a
Refrigerant Charge	g	40	40	40	40	40
Input Power	W	112	112	112	112	112
Voltage / Frequency	V/Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50
Energy Consumption	kWh/h	0,16	0,17	0,18	0,19	0,19
Internal Dimension (WxDxH)	mm	845 x 305 x 155	1145 x 305 x 155	1245 x 305 x 155	1445 x 305 x 155	1645 x 305 x 155
External Dimension (WxDxH)	mm	1200 x 395 x 260	1500 x 395 x 260	1600 x 395 x 260	1800 x 395 x 260	2000 x 395 x 260
Packed Dimension (WxDxH)	mm	1280 x 440 x 310	1580 x 440 x 310	1680 x 440 x 310	1880 x 440 x 310	2080 x 440 x 310
40ft Container Load	pcs	250	250	250	250	250